# **SATURN** 1000-E

Cedar Silicon's newly designed SATURN1000-E next generation mobile device offers unsurpassed multifunctional capabilities and optimizes the checkout process for your business. It comes with several optional features including 4G LTE, Wi-Fi, Bluetooth, microphone, rear camera, barcode reader, fingerprint reader, and a charging base.

The SATURN1000-E is based on a secure Android platform and has integrated contactless reader function with a 5" capacitive touchscreen. SATURN1000-E is extremely easy to use, safe and secure product for customers seeking an advanced next generation payment device.



- Secure Android Platform
- 5" Color Touch Screen
- Rear Camera

-011


- Fingerprint Reader
- Barcode Scanner




### FEATURES & BENEFITS

#### Unprecedented Security and Certifications

- PCI PTS 5.x
- EMV Contact/ Contactless Lv1
- EMV Contact Lv2
- Contactless Scheme Certifications (Paypass, Paywave, ExpressPay, D-PAS, J-Speedy, QPBOC ... )



- Optional barcode reader and fingerprint reader
- Accepts all payment types
- Flexible to integrate business applications



- **Highly Secure Processor**
- Operable under extreme ٠ conditions
- Android open architecture OS •

# SATURN 1000-E

## SPECIFICATIONS

SPECIFICATIONS			SATURN1000-E
Processor			High Speed Quad-Core CPU plus Secure MCU
Memory	Flash/RAM		8GB/1GB (Up to 16GB/2GB)
Display			5" Color TFTLCD with Capacitive Touch Panel   1280 x 720 Pixels
Card Reader	Magnetic Stripe		ISO 7810, 7811, 7813 Triple Track, Bi-Directional
	Contact Card	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1
		SAM Card	2
		SIM Card	2
	Contactless (Optional)		ISO 14443 Type A, B   ISO 18092 NFC   MiFare and Sony FeliCa Working Frequency 13.56MHz
Communications Interface Options	Wireless		4G LTE   Wi-Fi   Bluetooth
Indicators	Audio		Speaker and 4 Pole Audio Jack   Microphone
Keypad			Virtual Keypad (Support PIN on Touch)
Software			SDK   KMS   TMS   GDB   CTOS library ISO 8583 library   Crypto library
Crypto			TRNG   DES   T'DES   AES   RSA   MK/SK   DUKPT
Power Supply	DC		5V/2A
	Battery		Li-ion Rechargeable Battery 3.7V 3000mAh
Dimensions (mm)			169(L) x 75(W) x 18(H)
Weight			242 g
Environment	Operating Temperature		0°C to 50°C
	Storage Temperature		-20°C to 70°C
	Operating Humidity		5% to 90% non-condensing
	Storage Humidity		5% to 90% non-condensing
Certification			PCI PTS 5.X   EMV L1/L2   payWave   PayPass   ExperssPay D-PAS Interac Flash   J-Speedy   FeliCa   UnionPay UICS TQM   PBOC L1/L2
			EM Divels Boar Camera Studies Base

**Optional Additional Features** 

5M Pixels Rear Camera Stylus Base Fingerprint Reader Barcode Reader